

The Bravo fire pit is handmade by Dekko in North America. Ships with your choice of NG or LP burner, one decorative aggregate option and chrome On/Off key.

Size: 32"W x 32"D x 13"H CSA/UL Approved Burner Assembly



	Manual Ignition	Electronic Ignition
BTU/Hr	65,000	90,000
Weight	115 lbs	115 lbs
Fuel Options	NG/LP	NG/LP

Optional Accessories:

Propane Tank Cover 16"W x 16"D x 21"H Glass Wind Guard 23"D x 6"H

Vinyl Weather Cover

Powder Coated Aluminium Table Top 32"W x 32"D

Colour Options







NATURAL

ASH

SANDSTONE

CHARCOAL

Decorative Aggregate Options









IVORY BEACH STONE


SLATE BEACH STONE


BLACK LAVA ROCK





PERSPECTIVE VIEW






Overhead solid structure:



Clearances



Solid structure or combustible on no more than 2 sides.

- 12" minimum clearance for noncombustible materials.


Note

Deck Installation - a deck insulation kit is required when installing the fire pit on a wood or composite deck. Kit includes basalt material and instructions.

Burner Assembly

Min 54" - Max 144""


18" Match Lit Burner



Electronic Ignition

Clearances

Overhead solid structure: (Floor, overhang, pergola or screen)



Solid structure or combustible on no more than 2 sides.

- 12" minimum clearance for noncombustible materials.

Note: Electronic ignition burners require a fixed piping gas supply. Not for use with portable LP tanks.

Deck Installation - if installing fire pit on a wood or composite deck, it is required to use the deck insulation kit. Kit includes basalt material and instructions.

Burner Assembly

Electrical:

120V Outdoor receptacle required. Must be installed and grounded in accordance with local codes.

2 sides.

18" Electronic Ignition Burner

